

1. Identification

Product identifier: AQUASTOP FAST PART A
Other means of identification: ---
Recommended use: Floor coatings
Restriction on use: Any that differs from the recommended use
Supplier Name: U.S. Resin Supply & Manufacturing
1309 Coffeen Ave. suite 16257
Sheridan, Wyoming
United States, WY82801
Telephone: 307-336-0741
Available hours: 9 AM to 5 PM Monday to Friday

2. Hazard identification

Signal word: WARNING

Product classification:



Skin irritation - Category 2. Serious eye irritation - Category 2A. Skin sensitization - Category 1.

Hazard statement(s):
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.

Precautionary statement(s)

Prevention: Avoid breathing mist, vapours, and spray. Wash hands thoroughly after handling and any other part of the body that may have been exposed to the product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. If skin irritation or a rash occurs: Get medical advice. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

Storage: Not applicable

Disposal: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: Moderately toxic by intraperitoneal route.

See toxicological information, section 11

Safety Data Sheet

AQUASTOP FAST PART A

3. Composition / Information on ingredients

No	CAS No :	Common name and synonyms	Concentration % (w/w)
1	25068-38-6	Epichlorhydrin; bisphenol A, copolymer	65.00 - 88.00
2	13463-67-7	Titanium dioxide, rutile. (C.I. pigment white 6)	0.01 - 20.00
3	100-51-6	Benzyl alcohol. Benzenemethanol	3.00 - 7.00 *
4	398475-96-2	Alkylolammonium salt	0.01 - 2.00
5	1333-86-4	Carbon black. (C.I. pigment black 7)	0.01 - 1.00

* The actual concentration range is withheld as a trade secret.

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention as soon as possible.

Skin contact: Remove contaminated clothing immediately. Wash the skin with soap and water. Thoroughly wet contaminated clothing. If irritation persists, consult a doctor.

Inhalation: Move exposed person to fresh air. Keep this person warm and lying down. Loosen tight clothing such as a collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting unless instructed by medical personnel.

Symptoms: Red eyes, itching, blurred vision and tearing. Redness, flaking and cracking of the skin. The worker may develop cutaneous hypersensitivity.

Effects (acute or delayed): This product is a serious irritant that may cause reversible damages to the cornea. Possible erythema of the skin. May cause skin sensitization.

Immediate medical attention and special treatment: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: May release dangerous fumes. Evacuate the area. Fight fire from a safe distance or a protected location. Approach fire from upwind to avoid hazardous vapours or gases.

Hazardous combustion products: Hydrochloric acid and phosgen. Carbon monoxide and dioxide. Chlorides.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or if you do not have suitable training or protection. Evacuate surrounding areas. Do not touch or walk through spilled material. Shut off all heating and ignition sources. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution. Use inert absorbent or retention tubes in the event of a large spill.

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Contain leaks and pick up with non-combustible absorbent materials such as sand, earth or vermiculite. Then, place in an appropriate waste disposal container according to local regulations. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Strong acids and strong oxidizing agents.

Safety Data Sheet

AQUASTOP FAST PART A

8. Exposure Controls/ Personal protection

Control parameters:

Occupational exposure limit values:

United States

No	CAS No :	Common name and synonyms	IDLH NIOSH	Regulatory Limits			Recommended Limits	
				OSHA PEL		California / OSHA PEL	NIOSH REL	ACGIH ® 2019 TLV ®
				ppm	mg/m ³	8-hour TWA (ST) STEL (C) Ceiling	Up to 10-hour TWA (ST) STEL (C) Ceiling	8-hour TWA (ST) STEL (C) Ceiling
1	25068-38-6	Epichlorhydrin; bisphenol A, copolymer	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	13463-67-7	Titanium dioxide, rutile. (C.I. pigment white 6)	5000	Not listed	15	Not listed	Ca (ultrafine particles) 2.4 mg/m3 (fine) 0.3 mg/m3 (ultrafine)	10 mg/m3
3	100-51-6	Benzyl alcohol. Benzenemethanol	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	398475-96-2	Alkylolammonium salt	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
5	1333-86-4	Carbon black. (C.I. pigment black 7)	1750	Not listed	3.5	3.5 mg/m3	3.5 mg/m3 (without PAHs); when PAHs are present, NIOSH considers carbon black to be a potential occupational carcinogen.	3 mg/m3 (IHL)

IDLH: Immediately Dangerous to Life or Health Concentrations

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limits

California / OSHA: California Division of Occupational Safety and Health

REL: Recommended Exposure Limits

ACGIH ®: American Conference of Governmental Industrial Hygienists

TLV ®: Threshold Limit Values

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Safety Data Sheet

AQUASTOP FAST PART A

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES. Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.

9. Physical and chemical properties

Physical state: Liquid

Colour: Clear and/or various colors

Odour: Slight hydrocarbon smell

Melting/Freezing point: < -16 °C (3.2 °F)

Initial boiling point/boiling range: > 150 °C (302 °F)

Flammability: Not applicable

Lower flammable/explosive limit: Not applicable

Upper flammable/explosive limit: Not applicable

Flash point: > 100 °C (212 °F) Closed cup

Auto-ignition temperature: 288 °C (550.4 °F)

Decomposition temperature: 220 °C (428 °F)

pH: Not applicable

Kinematic viscosity: 415 - 696 mm²/s (at 40 °C)

Solubility (in water): Insoluble

Partition coefficient – n-octanol/water (Log Kow): > 1

Vapour pressure: < 0.1 mm Hg at 20 °C

Density and relative density: 1.151 - 1.329 kg/L at 20 °C (water = 1)

Relative vapour density: > 1 (air = 1)

Particle characteristics: Not applicable

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: This product is unstable under the following conditions: The product will degrade when exposed to light.

Possibility of hazardous reactions: May ignite if heated strongly and in the presence of an ignition source. May release toxic and corrosive products when heated.

Conditions to avoid: Keep away from incompatible products (see section 7). Some risk may be expected of corrosive and toxic decomposition products. To avoid thermal decomposition, do not overheat.

Incompatible materials: This product may attack certain metals.

Safety Data Sheet

AQUASTOP FAST PART A

Hazardous decomposition products: Carbon monoxide and dioxide. Chlorides.

11. Toxicological information

	Oral	Dermal	Inhalation gases	Inhalation vapours	Inhalation dusts/mists
ATE _{product}	5918.34 mg/kg	3926.44 mg/kg	N/A	> 20 mg/l	4.37 mg/l

No	CAS No :	Common name and synonyms	LD ₅₀ oral mg/kg	LD ₅₀ skin mg/kg	LC ₅₀ inhalation ppmV 4h - gases	LC ₅₀ inhalation mg/l 4h - vapours	LC ₅₀ inhalation mg/l 4h - dusts-mist
1	25068-38-6	Epichlorhydrin; bisphenol A, copolymer	11400	> 5000	N/A	> 20.00	> 5.00
2	13463-67-7	Titanium dioxide, rutile. (C.I. pigment white 6)	5000	5000	N/A	N/A	6.82
3	100-51-6	Benzyl alcohol. Benzenemethanol	1230	> 2000	N/A	> 20.00	> 5.00
4	398475-96-2	Alkylolammonium salt	> 5000	> 5000	N/A	> 20.00	> 5.00
5	1333-86-4	Carbon black. (C.I. pigment black 7)	> 8000	> 3000	N/A	N/A	6.75

Routes of exposure: This product is absorbed through the respiratory tract, skin and gastrointestinal tract.

Symptoms: Red eyes, itching, blurred vision and tearing. Redness, flaking and cracking of the skin. The worker may develop cutaneous hypersensitivity.

Delayed and immediate effects: This product is a serious irritant that may cause reversible damages to the cornea. Possible erythema of the skin. May cause skin sensitization.

Aspiration hazard	N/A
Skin corrosion - Skin irritation	Yes
Serious eye damage - Serious eye irritation - Eye irritation	Yes
Skin sensitization	Yes
Respiratory sensitization	N/A
Specific target organ toxicity – single exposure Category 3 Respiratory tract irritation	N/A
Specific target organ toxicity – single exposure	N/A
Specific target organ toxicity – single exposure Category 3 Narcotic effects	N/A
Specific target organ toxicity – repeated exposure	N/A

Safety Data Sheet

AQUASTOP FAST PART A

No	CAS No :	Common name and synonyms	IARC	ACGIH	Mutagenicity	Effect on reproduction
1	25068-38-6	Epichlorhydrin; bisphenol A, copolymer	Not listed	Not listed	The data do not allow for an adequate assessment of mutagenic effects.	No effects shown.
2	13463-67-7	Titanium dioxide, rutile. (C.I. pigment white 6)	2B	A3	No effects shown.	No effects shown.
3	100-51-6	Benzyl alcohol. Benzenemethanol	Not listed	Not listed	The data do not allow for an adequate assessment of mutagenic effects.	The data do not allow for an adequate evaluation of the effects on development.
4	398475-96-2	Alkylolammonium salt	Not listed	Not listed	No effects shown.	No effects shown.
5	1333-86-4	Carbon black. (C.I. pigment black 7)	2B	A3	No effects shown.	No effects shown.

Cancer classification under IARC (International Agency for Research on Cancer)

Group 1: carcinogenic to humans.
 Group 2A: probably carcinogenic to humans.
 Group 2B: possibly carcinogenic to humans.
 Group 3: not classifiable as to its carcinogenicity to humans.
 Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

Group A1: confirmed human carcinogen.
 Group A2: suspected human carcinogen.
 Group A3: confirmed animal carcinogen with unknown relevance to humans.
 Group A4: not classifiable as a human carcinogen.
 Group A5: not suspected as a human carcinogen.

Safety Data Sheet

AQUASTOP FAST PART A

12. Ecological information

Ecotoxicity

No	CAS No :	Common name and synonyms	%	Aquatic Ecotoxicity short term	Aquatic Ecotoxicity long term	Terrestrial Ecotoxicity
1	25068-38-6	Epichlorhydrin; bisphenol A, copolymer	65.00 - 88.00	Not available.	Toxic to aquatic life with long lasting effects.	Harmful to the environment.
2	13463-67-7	Titanium dioxide, rutile. (C.I. pigment white 6)	0.01 - 20.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
3	100-51-6	Benzyl alcohol. Benzenemethanol	3.00 - 7.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
4	398475-96-2	Alkylolammonium salt	0.01 - 2.00	Not available.	Toxic to aquatic life with long lasting effects.	Harmful to the environment.
5	1333-86-4	Carbon black. (C.I. pigment black 7)	0.01 - 1.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.

Persistence and degradability. Bioaccumulative potential. Other adverse effects

No	CAS No :	Common name and synonyms	%	Persistent	Bio-accumulation	Aquatic ecotoxicity
1	25068-38-6	Epichlorhydrin; bisphenol A, copolymer	65.00 - 88.00	Yes	No	Yes
2	13463-67-7	Titanium dioxide, rutile. (C.I. pigment white 6)	0.01 - 20.00	Yes	No	No
3	100-51-6	Benzyl alcohol. Benzenemethanol	3.00 - 7.00	No	No	No
4	398475-96-2	Alkylolammonium salt	0.01 - 2.00	N/A	N/A	N/A
5	1333-86-4	Carbon black. (C.I. pigment black 7)	0.01 - 1.00	Yes	No	No

Degradability: N/A

Mobility in soil: N/A

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

14. Transport information

	TDG	DOT	IMDG	IATA
UN Number	3082	3082	3082	3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epichlorhydrin; bisphenol A, copolymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epichlorhydrin; bisphenol A, copolymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epichlorhydrin; bisphenol A, copolymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epichlorhydrin; bisphenol A, copolymer)
Transport hazard class(es)	9	9	9	9
Packing group	III	III	III	III

Canada - ERAP

Not applicable

United States - Reportable Quantities (RQ)

Not applicable

Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78), and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)):
N/A

Marine pollutant: Yes

TDG: The identification of marine pollutant is not required for transport by ground.

IMDG: The mark « marine pollutant » is not required when the substance is carried in quantities ≤ 5L or ≤ 5 Kg.

Exemption for limited quantity: 5 L

In accordance with the Canadian Transport of Dangerous Goods regulations by Road, we use the 1.17 exemption when applicable. In accordance with 49 CFR article 172.315 for transportation by a mode other than air, we use the Limited quantities exemption when applicable.

Other exemptions: In Canada, containers of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S., are EXEMPT from the transport of dangerous goods on board a road vehicle, a railway vehicle or a vessel during a domestic journey according to special provision 99.

Special precautions: Not applicable

Safety Data Sheet

AQUASTOP FAST PART A

15. Regulatory information

United States

No	CAS No :	Common name and synonyms	%	TSCA	PROP-65	RTK
1	25068-38-6	Epichlorhydrin; bisphenol A, copolymer	65.00 - 88.00	X		
2	13463-67-7	Titanium dioxide, rutile. (C.I. pigment white 6)	0.01 - 20.00	X	X	X
3	100-51-6	Benzyl alcohol. Benzenemethanol	3.00 - 7.00	X		
4	398475-96-2	Alkylolammonium salt	0.01 - 2.00	X		
5	1333-86-4	Carbon black. (C.I. pigment black 7)	0.01 - 1.00	X	X	X

The classification of the product and the SDS were developed in accordance with HCS 2024.

This safety data sheet has been prepared for the following colors : Clear, Black, Tan, Beige, Light grey, Medium grey, White, RAL 7030, RAL 7012, Designer grey, Racing blue, Medium grey armor, Khaki tan, Desert tan.

16. Other information

Date: 2024-12-19

Version: 1

Notice to reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material supplier's. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.